

SOCKET SEN PG 11(28mm)

SEN-182/11 = PG-11-2Pole + Earth
SEN-183/11 = PG-11-3Pole + Earth
(Colour Black/Grey)



TECHNICAL SPECIFICATION

TECHNICAL SPECIFICATION

Contact Distance	18 mm	Insulation Class	AS PER VDE 0110-1/89
Nominal Voltage		Contact Mat.	Phosphor bronze Silver Plated
AC	Max.250V	Square Barrel	Brass, Silver Plated
DC	Max.300V	H.V.Breakdown Test	2KV AC for 1 min.
Nominal Current	10A	Gasket Material (Opt.)	Operating Temp.
Operation Current	16A	Nitrile/TPE	-40°C + 90°C
Contact Resistance	Max.20 m Ohms	Silicon	-40°C + 125°C
MAX.Conduc.Cross-Sect	1.5mm ²	Product Weight	29.00 gm
Body Material	Nylon (GF)	Packing	25 Nos. with fixing Screw & Gsk.
Cable (OD) PG9	4.5 - 7mm		

**TECHNICAL
SPECIFICATION**

Cable (OD) PG11

6 - 10mm

Carton Packing Domestic

500 Nos (25x20 packets)

Protection Class

IP 65 EN60529

Carton Packing Export

1000 Nos (25x40 packets)

TECHNICAL DIAGRAM

